EX-PRO HANDHELD PHONE

NSR's new Fire-fighter's portable radiotelephone:

- Meet IMO MSC.338 (91) and IMO MSC.1/Circ.1460/Rev.5 regulation
- Designed for onboard fire-fighter's communication
- 4-digit channels available
- Ex-proof certificated







According to IMO MSC.338 (91) & SOLAS Chapter II-2, regulation 10.10.5:

Fire-fighter's communication

A minimum of TWO two-way portable radiotelephone apparatus for each fire party for fire-fighter's communication shall be carried on board. Those two-way portable radiotelephone apparatus shall be of an explosion-proof type or intrinsically safe.



SPECIFICATIONS

• FREQUENCY & CHANNEL

- Frequency Range: 156.000∼161.450 MHz (TX)

156.000~163.425 MHz (RX)

- Channel Space: 25 kHz

- Usable Channels: Full ITU channels

• TECHNICAL FEATURE

- Output Power: High 3.0 W / Low 1.0 W

- Communication Methods: Simplex
- Warming Up Time: Within 5 sec
- Squelch Control:
√

- Squeich Control:
- Dual Watch:
- Key Locking:
- Battery Save Mode:
- Beep Establishment:
- Location Indication:

- V

- Ex Code: Ex ib II B T3 Gb
- Battery Capacity: 1800 mAh
- Battery Voltage: DC 7.4 V
- Operating Temperature: -20°C∼+60°C

- Size: $277.5 \text{ (H)} \times 60.8 \text{ (W)} \times 44.7 \text{ (D)} \text{ mm}$ - Weight: 300 g (Transceiver + Antenna + Battery)

150.5 127.0

EQUIPMENT LIST

STANDARD

- Transceiver & Antenna NTW-3000E 1 set - Rechargeable Battery Pack NBT800CX 1 pc - Battery Charger NBT800CU 1 pc - AC/DC Adaptor NBT200CUA 1 pc - Belt Clip 1 pc - Wrist Rope 1 pc

OPTIONS

- External PTT & Skull Mic/Headset NHS-500 1 set





Rechargeable Battery Pack

Belt Clip





AC/DC Adaptor





Wrist Rope







